


JIS B2401 (旧JIS W1517) O型圈 AN6230番 规格表
(圆筒面固定)
(航空器用O型圈油压用)



JIS 编号称呼	AS 568 编号称呼	O型圈尺寸		
		线径d2	内径d1	
1	006	1.78±0.07	2.9	±0.12
2	007		3.68	
3	008		4.47	
4	009		5.28	
5	010		6.07	
6	011		7.65	
7	012		9.25	
8	110	2.62±0.07	9.19	±0.12
9	111		10.77	
10	112		12.37	
11	113		13.94	
12	114		15.54	
13	115		17.12	
14	116		18.72	
15	210	3.53±0.10	18.64	±0.15
16	211		20.22	
17	212		21.82	
18	213		23.39	
19	214		24.99	
20	215		26.57	
21	216		28.17	
22	217	29.74		
23	218	5.33±0.12	31.34	±0.25
24	219		32.92	
25	220		34.52	
26	221		36.09	
27	222		37.69	
28	325		37.46	
29	326		40.64	
30	327	43.82		
31	328	5.33±0.12	46.99	±0.25
32	329		50.16	
33	330		53.34	
34	331		56.52	
35	332		59.69	
36	333		62.86	
37	334		66.04	
38	335	5.33±0.12	69.22	±0.38
39	336		72.39	
40	337		75.56	
41	338		78.74	
42	339		81.92	
43	340		85.09	
44	341		88.26	
45	342	91.44		

JIS 编号称呼	AS 568 编号称呼	O型圈尺寸		
		线径d2	内径d1	
46	343	5.33±0.12	94.62	±0.38
47	344		97.79	
48	345		100.96	
49	346		104.14	
50	347		107.32	
51	348		110.49	
52	349		113.66	
53	426	6.98±0.15	116.84	±0.58
54	427		120.02	
55	428		123.19	
56	429		126.36	
57	430		129.54	
58	431		132.72	
59	432		135.89	
60	433	6.98±0.15	139.06	±0.58
61	434		142.24	
62	435		145.42	
63	436		148.59	
64	437		151.76	
65	438		158.12	
66	439		164.46	
67	440	6.98±0.15	170.82	±0.76
68	441		177.16	
69	442		183.52	
70	443		189.86	
71	444		196.22	
72	445		202.56	
73	446		215.26	
74	447	6.98±0.15	227.96	±0.76
75	448		240.66	
76	449		253.36	
77	450		266.06	
78	451		278.76	
79	452		291.46	
80	453		304.16	
81	454	6.98±0.15	316.86	±0.38
82	455		329.56	
83	456		342.26	
84	457		354.96	
85	458		367.66	
86	459		380.36	
87	460		393.06	
88	425	113.66	±0.38	