



JIS B2401 O型圈 P番 规格表1  
(用于运动、圆筒面固定、平面固定)



JIS 编号称呼	O型圈尺寸	
	线径 d <sub>2</sub>	内径 d <sub>1</sub>
P 2	1.9±0.08	1.8 ±0.14
P 3		2.8 ±0.14
P 4		3.8 ±0.14
P 5		4.8 ±0.15
P 6		5.8 ±0.15
P 7		6.8 ±0.16
P 8		7.8 ±0.16
P 9		8.8 ±0.17
P 10		9.8 ±0.17
P 10A		2.4±0.09
P 11	10.8 ±0.18	
P 11.2	11 ±0.18	
P 12	11.8 ±0.19	
P 12.5	12.3 ±0.19	
P 14	13.8 ±0.19	
P 15	14.8 ±0.20	
P 16	15.8 ±0.20	
P 18	17.8 ±0.21	
P 20	19.8 ±0.22	
P 21	20.8 ±0.23	
P 22	21.8 ±0.24	
P 22A	3.5±0.1	21.7 ±0.24
P 22.4		22.1 ±0.24
P 24		23.7 ±0.24
P 25		24.7 ±0.25
P 25.5		25.2 ±0.25
P 26		25.7 ±0.26
P 28		27.7 ±0.28
P 29		28.7 ±0.29
P 29.5		29.2 ±0.29
P 30		29.7 ±0.29
P 31	3.5±0.1	30.7 ±0.30
P 31.5		31.2 ±0.31
P 32		31.7 ±0.31
P 34		33.7 ±0.33
P 35		34.7 ±0.34
P 35.5		35.2 ±0.34
P 36		35.7 ±0.34
P 38		37.7 ±0.37
P 39		38.7 ±0.37
P 40		39.7 ±0.37
P 41	40.7 ±0.38	
P 42	41.7 ±0.39	
P 44	43.7 ±0.41	
P 45	44.7 ±0.41	

JIS 编号称呼	O型圈尺寸	
	线径 d <sub>2</sub>	内径 d <sub>1</sub>
P 46	3.5±0.1	45.7 ±0.42
P 48		47.7 ±0.44
P 49		48.7 ±0.45
P 50		49.7 ±0.45
P 48A		5.7±0.13
P 50A	49.6 ±0.45	
P 52	51.6 ±0.47	
P 53	52.6 ±0.48	
P 55	54.6 ±0.49	
P 56	55.6 ±0.50	
P 58	57.6 ±0.52	
P 60	59.6 ±0.53	
P 62	61.6 ±0.55	
P 63	62.6 ±0.56	
P 65	64.6 ±0.57	
P 67	66.6 ±0.59	
P 70	69.6 ±0.61	
P 71	70.6 ±0.62	
P 75	74.6 ±0.65	
P 80	79.6 ±0.69	
P 85	8.4±0.15	84.6 ±0.73
P 90		89.6 ±0.77
P 95		94.6 ±0.81
P 100		99.6 ±0.84
P 102		101.6 ±0.85
P 105		104.6 ±0.87
P 110		109.6 ±0.91
P 112		111.6 ±0.92
P 115		114.6 ±0.94
P 120		119.6 ±0.98
P 125	124.6 ±1.01	
P 130	129.6 ±1.05	
P 132	131.6 ±1.06	
P 135	134.6 ±1.09	
P 140	139.6 ±1.12	
P 145	144.6 ±1.16	
P 150	149.6 ±1.19	
P 150A	8.4±0.15	14.95 ±1.19
P 155		154.5 ±1.23
P 160		159.5 ±1.26
P 165		164.5 ±1.30
P 170		169.5 ±1.33
P 175		174.5 ±1.37
P 180		179.5 ±1.40
P 185		184.5 ±1.44


JIS B2401 O型圈 P番 规格表2  
(用于运动, 圆筒面固定, 平面固定)



JIS 编号称呼	O型圈尺寸	
	线径 d <sub>2</sub>	内径 d <sub>1</sub>
*P 190	8.4 ± 0.15	189.5 ± 0.14
P 195		194.5 ± 0.14
P 200		199.5 ± 0.14
P 205		204.5 ± 0.15
P 209		208.5 ± 0.15
P 210		209.5 ± 0.16
P 215		214.5 ± 0.16
P 220		219.5 ± 0.17
P 225		224.5 ± 0.17
P 230		229.5 ± 0.17
P 235		234.5 ± 0.18
P 240		239.5 ± 0.18
P 245		244.5 ± 0.19
P 250		249.5 ± 0.19
P 255		254.5 ± 0.19
P 260		259.5 ± 0.20
P 265		264.5 ± 0.20
P 270		269.5 ± 0.21
P 275		274.5 ± 0.22
P 280		279.5 ± 0.23
P 285		284.5 ± 0.24
P 290		289.5 ± 0.24
P 295		294.5 ± 0.24
P 300		299.5 ± 0.24
*P 305		304.5 ± 0.25
*P 310		309.5 ± 0.25
P 315		314.5 ± 0.26
P 320		319.5 ± 0.28
*P 325		324.5 ± 0.29
*P 330		329.5 ± 0.29
P 335		334.5 ± 0.29
P 340		339.5 ± 0.30
*P 345		344.5 ± 0.31
*P 350		349.5 ± 0.31
P 355		354.5 ± 0.33
P 360		359.5 ± 0.34
*P 365		364.5 ± 0.34
*P 370		369.5 ± 0.34
P 375		374.5 ± 0.37
*P 380		379.5 ± 0.37
P 385	384.5 ± 0.37	
*P 390	389.5 ± 0.38	
*P 395	394.5 ± 0.39	
P 400	399.5 ± 0.41	
*P 405	404.5 ± 0.41	

JIS 编号称呼	O型圈尺寸		
	线径 d <sub>2</sub>	内径 d <sub>1</sub>	
*P 410	8.4 ± 0.15	409.5	± 3.00
*P 415		414.5	
*P 420		419.5	
*P 425		424.5	
*P 430		429.5	
*P 435		434.5	
*P 440		439.5	
*P 445		444.5	
*P 450		449.5	
*P 455		454.5	
*P 460		459.5	
*P 465		464.5	
*P 470		469.5	
*P 475		474.5	
*P 480		479.5	
*P 485		484.5	
*P 490		489.5	
*P 495		494.5	
*P 500		499.5	
*P 505		504.5	± 3.30
*P 510		509.5	
*P 515		514.5	
*P 520		519.5	
*P 525		524.5	
*P 530		529.5	
*P 535		534.5	
*P 540		539.5	
*P 545		544.5	
*P 550		549.5	
*P 555		554.5	
*P 560	559.5		
*P 565	564.5		
*P 570	569.5		
*P 575	574.5		
*P 580	579.5		
*P 585	584.5		
*P 590	589.5		
*P 595	594.5		
*P 600	599.5		
*P 610	8.4 ± 0.20	609.5	± 3.70
*P 620		619.5	
*P 630		629.5	
*P 640		639.5	
*P 650		649.5	
*P 660		659.5	
*P 610	8.4 ± 0.20	609.5	± 4.00
*P 620		619.5	
*P 630		629.5	
*P 640		639.5	
*P 650		649.5	
*P 660		659.5	
*P 610	8.4 ± 0.20	609.5	± 4.70
*P 620		619.5	
*P 630		629.5	
*P 640		639.5	
*P 650		649.5	
*P 660		659.5	

JIS B2401 O型圈 P番 规格表3  
(用于运动, 圆筒面固定, 平面固定)



JIS 编号称呼	O型圈尺寸	
	线径 d <sub>2</sub>	内径 d <sub>1</sub>
*P 670	8.4 ± 0.20	669.5
*P 680		679.5
*P 690		689.5
*P 700		699.5
*P 710		709.5
*P 720		719.5
*P 730		729.5
*P 740		739.5
*P 750		749.5
*P 760		759.5
*P 770		769.5
*P 780		779.5
*P 790		789.5
*P 800		799.5
*P 810		809.5
*P 820		819.5
*P 830		829.5
*P 840		839.5
*P 850		849.5
*P 860		859.5
*P 870		869.5
*P 880		879.5
*P 890		889.5
*P 900		899.5
*P 910		909.5
*P 920		919.5
*P 930		929.5
*P 940		939.5
*P 950		949.5
*P 960		959.5
*P 970	969.5	
*P 980	979.5	
*P 990	989.5	
*P 1000	999.5	
*P 1020	1019.5	
*P 1040	1039.5	
*P 1060	1059.5	
*P 1080	1079.5	
*P 1100	1099.5	
*P 1120	1119.5	
*P 1140	1139.5	
*P 1160	1159.5	
*P 1180	1179.5	
*P 1200	1199.5	
*P 1220	1219.5	

JIS 编号称呼	O型圈尺寸	
	线径 d <sub>2</sub>	内径 d <sub>1</sub>
*P 1240	8.4 ± 0.20	1239.5
*P 1260		1259.5
*P 1280		1279.5
*P 1300		1299.5
*P 1320		1319.5
*P 1340		1339.5
*P 1360		1359.5
*P 1380		1379.5
*P 1400		1399.5
*P 1420		1419.5
*P 1440		1439.5
*P 1460		1459.5
*P 1480		1479.5
*P 1500		1499.5