




## PPS工程塑料紧固件 聚苯硫醚 (Polyphenylenesulfide)

- 该材料为超级非结晶性工程塑料。具有耐热性，可在高温环境下长期使用不劣化。耐腐蚀性，机械性能，尺寸稳定性也非常优越，被广泛用于电气-电子产品，汽车零部件，
- 连续使用温度200℃ ● 燃烧性UL94 V-0

图片	名称 (编号)	规格								
		M2	M2.6	M3	M4	M5	M6	M8		
	盘头螺丝 (PPS/PH)	M2	M2.6	M3	M4	M5	M6	M8		
	节距	0.4	0.45	0.5	0.7	0.8	1	1.25		
	长度									
	4	○								
	5	○		○						
	6	○	○	○	○					
	8	○	○	○	○	○				
	10	○	○	○	○	○				
	12	○	○	○	○	○	○	○		
	15			○	○	○	○	○		
	16			○	○	○	○	○		
	18			○	○	○				
	20			○	○	○	○	○		
25			○	○	○	○	○			
30			○	○	○	○	○			
	埋头螺丝 (PPS/FH)			M3	M4	M5	M6			
	节距			0.5	0.7	0.8	1			
	长度									
	6			○						
	8			○	○					
	10			○	○	○	○			
	12			○	○	○	○			
	14				○					
	15			○	○	○	○			
	16			○	○					
	18				○					
20			○	○	○	○				
25			○	○	○	○				
30						○				
	外六角 螺丝 (PPS/BT)				M4	M5	M6	M8	M10	M12
	节距				0.7	0.8	1	1.25	1.5	1.75
	长度									
	8				○	○				
	10				○	○	○	○		
	12				○	○	○	○		
	15				○	○	○	○		
	20				○	○	○	○	○	○
	25				○	○	○	○	○	○
	30					○	○	○	○	○
35					○					
40						○	○	○	○	
50							○	○	○	